



AKS 150 L



AKB 150 L



AKSS 150 L

Technical features AKS 150 L / AKB 150 L / AKSS 150 L



	AKS 150 L	AKB 150 L	AKSS 150 L
Code	0901069	0901066	0901072
Connectors	F male – F male	IEC male – IEC female	F male – IEC male
Length	1.5 m	1.5 m	1.5 m
Inner Conductor (mm) ø	1.0 Cu	1.0 Cu	1.0 Cu
Dielectric (mm) ø	4.6 PE	4.6 PE	4.6 PE
Foil	Al / Pet / Al	Al / Pet / Al	Al / Pet / Al
Braid material	Al	Al	Al
Braid (n° of wires)	128	128	128
Second foil	Al / Pet	Al / Pet	Al / Pet
Screening factor (30-900 MHz)	> 110 dB	> 110 dB	> 110 dB
Jacket outer diameter (mm) ø	7.06	7.06	7.06
Jacket	PVC white	PVC white	PVC white
Impedance	75 Ohms	75 Ohms	75 Ohms
Type	Trishield	Trishield	Trishield





AKS 250 L



AKB 250 L

Technical features AKS 250 L / AKB 250 L



	AKS 250 L	AKB 250 L
Code	0901070	0901067
Connectors	F male – F male	IEC male – IEC female
Length	2.5 m	2.5 m
Inner Conductor (mm) ø	1.0 Cu	1.0 Cu
Dielectric (mm) ø	4.6 PE	4.6 PE
Foil	Al / Pet / Al	Al / Pet / Al
Braid material	Al	Al
Braid (n° of wires)	128	128
Second foil	Al / Pet	Al / Pet
Screening factor (30-900 MHz)	> 110 dB	> 110 dB
Jacket outer diameter (mm) ø	7.06	7.06
Jacket	PVC white	PVC white
Impedance	75 Ohms	75 Ohms
Type	Trishield	Trishield



AKS 500 L



AKB 500 L

Technical features AKS 500 L / AKB 500 L



	AKS 500 L	AKB 500 L
Code	0901071	0901068
Connectors	F male – F male	IEC male – IEC female
Length	5 m	5 m
Inner Conductor (mm) ø	1.0 Cu	1.0 Cu
Dielectric (mm) ø	4.6 PE	4.6 PE
Foil	Al / Pet / Al	Al / Pet / Al
Braid material	Al	Al
Braid (n° of wires)	128	128
Second foil	Al / Pet	Al / Pet
Screening factor (30-900 MHz)	> 110 dB	> 110 dB
Jacket outer diameter (mm) ø	7.06	7.06
Jacket	PVC white	PVC white
Impedance	75 Ohms	75 Ohms
Type	Trishield	Trishield