


K 200 E



K 200 E - K 200 E3

Technical specifications. 6,8 mm coaxial cable K 200 E

	K 200 E	K 200 E3
Code	0703121	0703121-3
Inner conductor (mm) Ø	1,0 CCS	1,0 CCS
Dielectric (mm) Ø	4,6 PE	4,6 PE
Foil material	Al / Pet	Al / Pet
Braiding material	Al	Al
Number of wires (braiding)	48	48
Braiding composition	16 x 3 x 0,12 mm	16 x 3 x 0,12 mm
Braiding coverage	40 %	40 %
Outer jacket (mm) Ø	6,8 PVC white	6,8 PVC white
Screening factor (30 - 900 MHz)	> 70 dB	> 70 dB
Nominal attenuation (dB / 100 m)	47 MHz	4,8
	175 MHz	8,3
	470 MHz	13,5
	862 MHz	18,8
	950 MHz	19,9
	1350 MHz	24,0
	1750 MHz	27,5
	2150 MHz	30,9
Lenght (m)	100	300
Impedance (Ω)	75	75
Net weight (Kg)	3,57	10,71
Reaction to fire	Fca	Fca
No. Declaration of Performance (DoP)	DOP-0703121	DOP-0703121-3
Presentation	100 m giftbox	300 m wooden drum
EAN Code 13	8436023597890	8436023599368
Packaging quantity	1 / 4	1