



Technical Features MAX T110

Sleep Timer	Teletext	Update through RS 232
FTA free channels	Games	Power Supply 5 Vdc for active indoor antenna
OSD multi-language	4000 channels	Low power consumption LPC
3 x RCA AV	1 Scart	
Electronic Program Guide (EPG)	TV-Radio	

Commercial and logistic information

Measures: 240x50x190 mm	Code: 0710018
Weight: 1,2 kg	Packaging: 6 pcs

MAX T110

1 Scart
3 x RCA AV
LPC: Low Power Consumption
FTA: free channels



Digital Terrestrial Receivers MAX T110

VIDEO	
Decoding Bit rate Output Aspect ratio Active pixel Output connector	MPEG-2 & MPEG-1 compatible Max 15Mbps PAL/NTSC 4:3, 16:9, Auto 720x480 @ 30fps; 720x576 @25fps Scart /RCA
AUDIO	
Decoding Sampling rate Output connector	MPEG-2/MPEG-1 layer I & II 32 /44,1/ 48 Khz Scart / RCA
INPUT SIGNAL	
Demodulation Guard	COFDM 2k, 8k 1/4, 1/8 , 1/16, 1/32
SIGNAL	
Frequency Input	VHF-UHF 32 - 90 dBuV
MISCELLANEOUS	
Supply voltage Power consumption Operation temperature Storage temperature Dimension Weight	100~240VAC 50~60 Hz Typ. 21 watts / Max. 30 watts +5° to +40° -20° to +70° 240 x 50 x 190 mm 1,2 Kg