



Technical Features MAX T180

Sleep Timer	Teletext	3 x RCA AV
FTA free channels	Games	SPDIF: Coxial Audio Digital Output
Updated through RS 232	2 Scart	4000 channels
OSD multi-language + display	TV-Radio	Modulator C21-C69
Electronic Program Guide (EPG)	Power Supply 5 Vdc for active indoor antenna	

Commercial and logistic information

Measures: 240x190x45 mm	Code: 0710012
Weight: 1,1 kg	Packaging: 6 pcs

MAX T180

4000 channels ,
FTA free channels,
2 scart, SPDIF,
3 X RCA AV,
7 Front panel buttons

4000
channels

FTA

2
SCART

SPDIF

3X
RCA AV

7
buttons



Digital Terrestrial Receivers MAX T180

VIDEO	
Decoding Bit Rate Output Screen format Resolution Connections	MPEG-2 & MPEG-1 compatible Max 15Mbps NTSC/ SECAM / PAL 4:3, 16:9, Auto 720x480 @ 30fps; 720x576 @25fps Scart o RCA
AUDIO	
Decoding Sampling rate Connections	MPEG-2/MPEG-1 layer I & II 32 /44,1/ 48 Khz Scart, RCA, AC3 coaxial
DEMODULATION	
Demodulation Guard Input data rate	COFDM 2k, 8k 1/4, 1/8 , 1/16, 1/32 2-45 MS/s
INPUT SIGNAL	
Frequency range Input level	VHF-UHF -78dBm -20dBm
RF MODULATOR	
Band TV Standard Output channels	UHF C21-69 PAL BG / I / DK, NTSC 21~69 (PAL), 14~83 (NTSC)
DIVERS	
Current supply for active antenna Power supply Power consumption Operation temperature Size Weight	5V / 75mA 90~260VAC 50Hz~60Hz Typ. 15 watts +5° to +40° 240x190x45 mm 1,1 Kg

